

EN Energy label CKASE

Product description		
Classic cooktop extractor system with ULS25 plinth fan	CKASE	
Operating mode	Exhaust air	
Energy consumption	Value	EN standard
Annual energy consumption (AEC _{hood})	24 kWh/a	61591
Energy efficiency class	A++	61591
Flow volume		
Fluid dynamic efficiency (FDE _{hood})	38.4	61591
Fluid dynamic efficiency class	A	61591
Lighting		
Lighting efficiency (LE _{hood})	* lx/Watt	*
Lighting efficiency class	*	*
Grease filtering		
Level 5 maximum (GFE _{hood})	47%	61591
Class level 5 normal	F	61591
Flow volume		
Air flow level 1 minimum	224 m ³ /h	61591
Air flow level 5 maximum (Q _{max})	609 m ³ /h	61591
Sound power level		
Level 1 minimum	46 dB(A)	60704-2-13
Level 5 maximum	67 dB(A)	60704-2-13
Sound pressure level (additional details)		
Level 1 minimum	33 dB(A)	**
Level 5 maximum	55 dB(A)	**
Details according to 66/2014		
Power consumption in off mode (P _o)	< 0.5 W	61591
Time increase factor	0.6	61591
Energy efficiency index (EEI _{hood})	31.7	61591
Air flow rate at the best efficiency point (Q _{BEP})	280.8 m ³ /h	61591
Pressure at the best efficiency point (P _{BEP})	536 Pa	61591
Electric power input at the best efficiency point (W _{BEP})	109 W	61591

Energy label information

* This specification is not applicable for this product.

** The sound pressure level has been determined from a distance of 1 m (distance-dependent level recording) on the basis of the sound power level established in EN 60704-2-13.