



**technical data**

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.7 kW
Maximum power rating	3.7 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, (switching 2-ring/Hyper)
Weight (incl. accessories/packaging)	7.2 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	327 x 515 x 75 mm
Front cooking zone dimensions	Ø 215 mm
Front cooking zone power	2100 W
Front cooking zone power setting	3000 W
Number of cooking zone circuits front	1
Back cooking zone dimensions	Ø 120/180 mm
Back cooking zone power	600 W/1600 W
Number of cooking zone circuits rear	2

**Product description**

- Free choice of cooktop
- Super fast parboiling
- 2-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function
- residual heat display

**Scope of delivery**

- Hyper glass ceramic cooktop CKCH
- glass ceramic scraper
- mounting straps
- height adjustment plate set

**product- and planning instructions**

- Ensure sufficient ventilation of the area below the cooktop.